




MODEL: SC24P00-DDR+TB

DESCRIPTION	PART NO. & SPECIFICATION
Fork Length	100mm SUS316L
Operating Temp	-40~100°C
Operation Pressure	Max. 40Bar
Material Density	Solid: 0.07g/cm ³ Liquid: 0.7g/cm ³
Viscosity	1~10,000 cSt
Housing material	SUS304
Connection	1"PF (G)
Electrical Connection	DIN 43650
Supply Voltage & Output	12~55Vdc 3 Wire PNP Output

*With O-Ring(part no:27-3037-V)

VIBRATING PROBE LEVEL SWITCH

Order code: SCX20000-ABPAAA803MAD0130T01

Copyright, without permission, is prohibited reproduction, retained or circulated Rights Reserved.



FineTek Co., Ltd.
e-mail: info@fine-tek.com
http://www.fine-tek.com

SA
APPROVED

[Signature]

APPROVED
BY CLIENT

SALES

[Signature]

RD/PR
APPROVED

Fish.Cheng

MODEL:

SC24P00-DDR+TB

DRAWING

Shengyao

DATE:
2020.08.11

UNIT: mm
SCALE: 1:2

REV.
D0



Tuning Fork Level Switch



PRODUCT INTRODUCTION

WORKING PRINCIPLE

The SC series is a vibrating tuning fork point level sensor that utilizes piezoelectric crystal and solidstate electronics technology to produce vibration in the tuning fork element at a specific frequency and receive electronic feedback. When the probe element is in contact with the target material, the vibration is dampened, the electronic feedback changes, and presence of the material is thereby sensed by the electronics which changes the state of the sensor output to indicate material presence. When the probe element is again free of the target material, the vibration again is produced and the output state reverts to indicate material absence.

FEATURE

- SPDT Relay output, SSR MOSFET output.
- Wide voltage supply range 20~250 Vac/Vdc,50/60Hz
- No frequent calibration required, easy-to-use, sturdy and durable design. High/low failure safe mode, safe and reliable.
- Sensitivity adjustment is available for different densities of media. Fine powder can be detected.
- Suitable for liquid, powder, and solid application.
- Dual insulation can reduce damage on the PCB board caused by great changes in temperature and humidity, as well as condensation effects (SC3□ series).
- It can be tested by pressing the test button after installation (SC3□ series).
- Output switch delay function (SC3□ series).
- Self-diagnosis mechanism can detect the abnormality such as the abrasion of the tuning fork or the material viscosity (SC3□ series).
- The compact built-in wiring box can save the installation space (SC3□ series).
- The wiring box can rotate 270 degrees, facilitating adjustment of the inlet direction (SC3□ series).
- The minimum measurable specific gravity can reach 0.01 g/cm³ (SC35 series).
- Ultra protection mechanism can set the secondary output contact point as alarm output (SC35 series).
- Support the function of detecting underwater sediments (SC35 series).
- All-in-one design, 3/4" (SC38), 1" thread is suitable for the installation of a small tube.
- Adjustment setting for different densities of media P>0.5 g/cm³ or ρ.0.7 g/cm³ (SC38).
- Switch delay setting function (SC3□ series).
- Alarm indicators based on failure status or output status selected according to the customer's habits (SC3□ series).
- Automatic calibration of the operation points for different densities of media as required by the customer (SC38).

APPLICABLE MATERIALS

The tuning fork level switch can be widely applied to detect the min. and max. level in tanks, silos and hoppers filled with materials of different densities and state. The following is a list of applications.

POWDER

- | | |
|------------------------|------------------------|
| 1. Powdered milk | 15. Pellets |
| 2. Frozen potato chips | 16. Peanuts |
| 3. Beans | 17. Tobacco |
| 4. Sugar | 18. Wood shavings |
| 5. Sweets | 19. Chalk |
| 6. Coffee beans | 20. Stearin chips |
| 7. Coffee powder | 21. Powdered cellulose |
| 8. Frozen dry coffee | 22. Glass fine power |
| 9. Tea | 23. Granular plastics |
| 10. Salt | 24. Gravel |
| 11. Flour | 25. Powdered clay |
| 12. Foundry sand | 26. Polystyrene powder |
| 13. Spices | 27. Styrofoam |
| 14. Animal food | 28. Soda |

LIQUID

1. Water & Solutions
2. General Purpose Solvent
3. Soy sauce
4. Heavy oil
5. Petroleum
6. Oil
7. Ink
8. Cream
9. Drink & Beverage
10. Corrosive liquid

APPLICATION SCOPE

It is applicable to the max. and min. level detection of the tanks or tubes filled with various solid/liquid media. The product has a variety of applications, such as in the chemical fiber industry, rubber industry, tire industry, cement industry, steel industry, food industry, pharmaceutical industry, and animal feed factories in terms of the level detection for the bins of the raw material/process/finished products.




APPLICATION EXAMPLE

Application situation	SC24	SC28	SC14X	SC17X	SC35X	SC38X
Liquid	★	★	★	★		★
Powder	★		★	★	★	
Solid					★	
Corrosive media			Optional			
Explosion proof				★	★	★
Tri-Clamp connection	Optional	Optional	Optional			
Operation temp. 100°C	★	★				
Operation temp. 130°C			★	★		
Operation temp. 150°C					★	★
Operation temp. 280°C					★	
Max. pressure<25Bar					★	
Max. pressure<40Bar	★	★	★	★		★
Max. pressure<60Bar						




LITE-TYPE

Dimensions (Unit:mm)				
Model no.	SC24□□□ 【DIN Connector】		SC24□□□ 【M12 Connector】	SC24□□□ 【Cable Wire Type】
Supply voltage & output	SC240□□: 20~250Vac / Vdc 2 Wire Contactless electronic switch. SC24P□□: 12~55Vdc 3 Wire PNP output. SC24N□□: 12~55Vdc 3 Wire NPN output.			
Fork length	100mm			
Ambient temp.	-40~85°C			
Ambient humidity	80% RH non-condensed			
Process temp.	SC24□□□T: -40~+150°C SC24□□□: -40~+100°C			
Process pressure	Maximum 40 Bar			
Min. material density sensed	Solid: density: ≥0.07g/cm ³ Liquid: density: ≥0.7g/cm ³ Viscosity: 1~10000 cSt			
Magnetic testing	Output function test performed by putting magnets near the indicated spot			
Vibrating frequency	350~370Hz			
Status indication	Green light:indicate power supply Red light:indicate operating mode			
Housing material	SUS304			
Probe material	SUS304, SUS316, SUS316L			
IP protection	IP65	IP67	IP67	
Mounting	1" more			
Conduit	Valve plug DIN 43650	M12 Connector(180° / 90°)	Cable connector	



MINI-TYPE

Dimensions (Unit:mm)						
Model no.	SC28□□□ 【DIN Connector】		SC28□□□ 【M12 Connector】		SC28□□□ 【Cable Wire Type】	
Supply voltage & output	SC280□□: 20~250,50/60Hz Vac/Vdc 2 Wire Contactless electronic switch. SC28P□□: 12~55Vdc 3 Wire PNP output. SC28N□□: 12~55Vdc 3 Wire NPN output.					
Fork length	40mm					
Ambient temp.	-40℃~85℃					
Ambient humidity	80% RH non-condensed					
Process temp.	SC28□□□T: -40℃~150℃ SC28□□□: -40℃~100℃					
Process pressure	-1~600PSI (40BAR)					
Min. material density sensed	Liquid:density: ≥0.7g/cm ³ Viscosity: 1~10000 cSt					
Magnetic testing	Output function test performed by putting magnets near the indicated spot					
Vibrating frequency	1 KHz± 10%					
Status indication	Green light:indicate power supply Red light:indicate operating mode					
Housing material	SUS304					
Probe material	SUS304, SUS316, SUS316L					
IP protection	IP65		IP67		IP67	
Mounting	3/4"more					
Conduit	Valve plug DIN 43650		M12 Connector(180° / 90°)		Cable connector	

STANDARD TYPE

Dimensions (Unit:mm)			
Model No.	SC1400 【Standard Type】	SC1410 【Tuning Fork Ultra Extension Type】	SC1420 【Tuning Fork Extension Type】
Level sensor housing	Aluminum / IP65		
Probe material	SUS 304 / 316 / 316L		
Mounting	1"PT		
Conduit	1/2"NPT × 2		
Max. vertical load on rod.	177in.Lbs(20Nm)		
Process pressure.	-1~600PSI (40BAR)		
Power supply	20~250Vac / Vdc,50 / 60Hz		
Power consumption	10VA		
Ambient temp.	-40°C~60°C		
Process temp.	-40°C~130°C		
Signal output	Relay, SPDT, 5A/250Vac / 28Vdc, 1 set or 2 set SSR(MOSFET) 400mA/60 Vac / Vdc, 1 set or 2 set		
Min. material density sensed	Solid: ≥0.07g/cm ³ , Liquid: ≥0.7g/cm ³		
Time delay	0.6 Second / Operate; 1~3 Seconds / Reset		
Vibrating frequency.	350~370Hz		
Selectable Fail-safe	Hi. / Lo.		
Selectable sensitivity	Hi. / Lo.		

EX-PROOF TYPE

Dimensions (Unit:mm)		
Model No.	SC1740 【Standard Type】	SC1741 【Tuning Fork Ultra Extension Type】
Level sensor housing	Aluminum / IP65	
Probe material	SUS 304 / 316 / 316L	
Mounting	1"PT	1"PT
Conduit	1/2"NPT×2	
Max. vertical load on rod.	177in.Lbs(20Nm)	
Process pressure.	-1~600PSI (40BAR)	
Power supply	20~250,50/60Hz Vac/Vdc	
Power consumption	10VA	
Ambient temp.	-20°C~70°C	
Process temp.	-40°C~125°C	
Signal output	Relay, SPDT, 3A / 250Vac / 28Vdc, 1 set or 2 set SSR(MOSFET) 400mA/60 Vac / Vdc, 1 set or 2 set	
Min. material density sensed	Solid: ≥0.07g/cm ³ , Liquid: ≥0.7g/cm ³ , viscosity : 1~10000 cst	
Time delay	0.6 Second / Operate; 1~3 Seconds / Reset	
Vibrating frequency.	350~370Hz	
Selectable Fail-safe	Hi. / Lo.	
Selectable sensitivity	Hi. / Lo.	

SC35 TUNING FORK LEVEL SWITCH



NEPSI Ex tD A21 IP66/67 T80°C / T95°C / T130°C / T195°C / T290°C
IECEx Ex ta IIIC T95°C / T130°C / T136°C Da
Ex tb IIIC T80°C / T95°C / T130°C / T160°C / T240°C / T290°C Db

Dimensions (Unit:mm)			
Model No.	SC350 【Standard Type】	SC351 【Extension Type】	SC352 【Cable Type】
Level sensor housing	Built-in box, aluminum coating IP66/IP67		
Probe material	SUS 304 / 316 / 316L		
Power supply	19 ~253 Vdc / Vac, 50/60 Hz ; NPN / PNP(10~55Vdc)		
Probe construction	Max. 1.5 W		
Voltage endurance capability	3.7 kV		
Overvoltage protection	overvoltage category II		
Ambient temp.	-40~85 °C		-40~75 °C
Process temp.	-40~150 °C	-40~150 °C	-40~80 °C
Material density	$\geq 0.01 \text{ g/cm}^3$ or $\geq 0.05 \text{ g/cm}^3$		
Measuring frequency	140 Hz $\pm$ 5 Hz		
Material dimension	Max.10 mm		
Conduit	1/2"PF / 1/2"NPT(Ex-proof type only supports 1/2"NPT)		
External diameter of conduit cable	$\phi 6 \sim \phi 10 \text{ mm}$		
Process pressure	Max.25 Bar		Max. 2 Bar
Output signal	2 sets of SPDT relay output / 2 sets of transistor output / 3 wires NPN/PNP transistor output		
Contact capacity	Relay: 6A / 250Vac , 6A / 28Vdc ; Transistor: 350mA , 60Vac / Vdc NPN / PNP / Transistor: 350mA , 55Vdc		

SC35 TUNING FORK LEVEL SWITCH



NEPSI Ex tD A21 IP66/67 T80°C / T95°C / T130°C / T195°C / T290°C
IECEX Ex ta IIIC T95°C / T130°C / T136°C Da
Ex tb IIIC T80°C / T95°C / T130°C / T160°C / T240°C / T290°C Db

Dimensions (Unit:mm)		
Model No.	SC350 [High-temp. Type]	SC351 [High-temp. Extension Type]
Level sensor housing	Built-in box, aluminum coating IP66/IP67	
Probe material	SUS 304 / 316 / 316L	
Power supply	19 ~253 Vdc / Vac, 50/60 Hz	
Probe construction	Max. 1.5 W	
Voltage endurance capability	3.7 kV	
Overvoltage protection	overvoltage category II	
Ambient temp.	-40~85 °C	
Process temp.	-40~280 °C	
Material density	$\geq 0.01 \text{ g/cm}^3$ or $\geq 0.05 \text{ g/cm}^3$	
Measuring frequency	140 Hz $\pm$ 5 Hz	
Material dimension	Max.10 mm	
Conduit	1/2"PF / 1/2"NPT(Ex-proof type only supports 1/2"NPT)	
External diameter of conduit cable	$\phi 6 \sim \phi 10 \text{ mm}$	
Process pressure	Max. 25 Bar	
Output signal	2 sets of SPDT relay output / 2 sets of transistor output	
Contact capacity	Relay: 6A / 250Vac , 6A / 28Vdc Transistor: 350mA , 60Vac / Vdc	

SC38 MULTI-FUNCTIONAL TUNING FORK LEVEL SWITCH



NEPSI Ex ia IIC T3~T6 Ga

Dimensions (Unit:mm)	SC380 【Standard Type】	SC381 【Extension Type】	SC382 【Ultra Extension Type】
-------------------------	----------------------------------	-----------------------------------	---

Output type	 8/16mA output type	3 Wires (NPN/PNP) output type	Dual-relay output type
Working voltage	11 ~36 Vdc	10 ~55 Vdc	19~253Vac / 2dc,50 / 260Hz
Power consumption	< 600mW	< 830mW	Max. 1.3W
Input protection	Reversed power supply protection function		NA
Overvoltage protection	overvoltage category III		
Measuring error	Max.±1mm		
Repeatability	0.5mm		
Hysteresis band	Approx.2mm		
Ambient temp.	-40~85 °C (Intrinsically safe type -40~70 °C)	-40~85 °C(Refernce operation manual)	
Process temp.	-40~150 °C		
Applicable density liquid	≥0.5 g/cm ³ or ≥0.7 g/cm ³		
Liquid viscosity	Max.10000mm ² / S(10000cst)		
Granule size contained in the liquid	Max.φ5 mm		
External diameter of conduit cable	φ6~φ10 mm		
Process pressure	Max.40 Bar		
Output signal	Intrinsically safe signal 8 / 216mA	Transistor output (NPN/PNP)	2 sets of SPDT relay output
Contact capacity	NA	350mA , 55Vdc	6A / 250Vac , 6A / 28Vdc
Protection level	IP66/67		
Probe material	SUS 304 / 2316 / 316L		
Intrinsically safe parameters	Ui(V)=36V , li=100mA,Pi=1W Ci(nF)=0 , Li(uH)=0※	NA	NA

※ Must be equipped with intrinsic safety barrier to form a standard intrinsically safe system (Ex ia), please refer to another DM/brochure for TXX safety barrier.

SC38 MULTI-FUNCTIONAL TUNING FORK LEVEL SWITCH



NEPSI Ex ia IIC T3~T6 Ga


Dimensions (Unit:mm)	SC380 【 High-temp. Type 】	SC381 【 High-temp. Extension Type 】	SC382 【 High-temp. Extension Type 】
-------------------------	---	---	---

Output type	8/16mA output type	3 Wires (NPN/PNP) output type	Dual-relay output type
Working voltage	11 ~36 Vdc	10 ~55 Vdc	19~253Vac/dc,50/60Hz
Power consumption	< 600mW	< 830mW	Max. 1.3W
Input protection	Reversed power supply protection function		NA
Overvoltage protection	overvoltage category III		
Measuring error	Max.±1mm		
Repeatability	0.5mm		
Hysteresis band	Approx.2mm		
Ambient temp.	-40~85 °C(Refernce operation manual)		
Process temp.	-40~150 °C		
Applicable density liquid	$\geq 0.5 \text{ g/cm}^3$ or $\geq 0.7 \text{ g/cm}^3$		
Liquid viscosity	Max.10000mm ² / S(10000cst)		
Granule size contained in the liquid	Max.φ5 mm		
External diameter of conduit cable	φ6~φ10 mm		
Process pressure	Max.40 Bar		
Output signal	Intrinsically safe signal 8/16mA	Transistor output (NPN/PNP)	2 sets of SPDT relay output
Contact capacity	NA	350mA , 55Vdc	6A / 250Vac , 6A / 28Vdc
Protection level	IP66/67		
Probe material	SUS 304 / 316 / 316L		
Intrinsically safe parameters	Ui(V)=36V , li=100mA,Pi=1W Ci(nF)=0 , Li(uH)=0※	NA	NA


※ Must be equipped with intrinsic safety barrier to form a standard intrinsically safe system (Ex ia), please refer to another DM/brochure for TXX safety barrier.

WIRING INSTRUCTIONS (STANDARD TYPE)

SC14XX, SC174X




SPDT Type



DPDT Type


Relay output type(SPDT)

SSR(MOSFET) output type



Relay output type (DPDT)

SSR(MOSFET) output type



FUNCTIONAL DESCRIPTION

Description of terminal functions

- L+, N-: Power Supply
- NC, COM, NO: Relay Output
- RT1, RT2: Remote-Test
- : Ground Connection
- COM1, NO1 : SSR(MOSFET) Output
- COM2, NO2 : The second set of SSR (MOSFET) output (Optional)

DESCRIPTION OF PANEL FUNCTIONS

- PWR: Power Supply (Green Light)
- SIGNAL: Output Indication (Red Light)
- FSH: Power On. The signal lamp is on and the relay is conductive. While the tuning fork switch senses the material, the signal lamp is off and relay is not conductive.
- FSL: Power On. The signal lamp is off and the relay is not conductive. While the tuning fork switch senses the material, the signal lamp is on and relay is conductive.
- SENSITIVITY L: Low Sensitivity
- SENSITIVITY H: High Sensitivity

FAIL-SAFE HIGH / LOW PROTECTION

FSH (Fail-Safe High) Protection:

Switch to FSH mode.

Normal Status: The signal lamp is on. It indicates that the tuning fork switch does not sense the material and the relay is conductive.

Failure: When the power shuts down, the signal lamp is off. It indicates that the tuning fork switch is voided and the relay is not conductive.

FSL (Fail-Safe Low) Protection:

Switch to FSL mode.

Normal Status: The signal lamp is on.

The tuning fork switch senses the material and the relay is conductive.

Failure: When the power shuts down, the signal lamp is off. The tuning fork switch is voided and the relay is not conductive.

SENSITIVITY ADJUSTMENT

The SENSITIVITY is located on the right side of the panel. Minor adjustment can be made by rotating the sensitivity up to 22 turns using a small screw driver. Rotating clockwise will increase sensitivity; rotating counter-clockwise will decrease sensitivity.

The sensitivity is originally set at max. value. The switching point is at 15mm from the tip of the tuning fork. The switching point position will be changed by the sensitivity value. If the sensitivity adjusts to lower value, the switching point position is moving backward; if the sensitivity adjusts to high value, the switching point position is moving forward. User may change the switching point position by adjusting the sensitivity. The changing range of switching point is about 60mm. For example, if the switching point needs to be moved backward by 30mm, the user needs to adjust SENSITIVITY counter-clockwise by 10 turns. In general cases, there is no need for sensitivity adjustment.

Level	FSL		FSH	
Contact form				
Indication				
Status	Fail	Normal	Normal	Fail

WIRING INSTRUCTIONS (LITE-TYPE/MINI-TYPE)

SC240X/SC280(TWO WIRES) WIRING





Figure 1 Two Wires Wiring



DIN Wiring Diagram

M12x4Pin Cable Wiring Diagram

Wiring

Power can be AC/DC switching. Two wires are connected with terminals (L+/N-) as in Figure 1.

■ Low (Min.) mode:

Pin 1 (Brown) is connected to N-. Pin 2 (Black) is connected to L+ with relay. Pin 4 (Yellow Green) connects to tank ground.

■ High (Max.) mode:

Pin 1 (Brown) is connected to N-. Pin 3 is connected to pin 2 (Black) to L+ with Relay. Pin 4 (Yellow Green) connects to tank ground.

WIRING INSTRUCTIONS (LITE-TYPE/MINI-TYPE)

SC24P/N,SC28P/N (THREE WIRES) WIRING




Figure 2 PNP / NPN Output Wiring Diagram

Wiring

Power supply is for DC only. Output is PNP / NPN and high / low level alarm. Please see Figure 2.

► DIN & Cable Wiring

PNP Output

- High (Max.) Mode: Pin 1(Brown) connects to N-. Pin 3 (Blue) connects to L+. To output, it is pin 2. (Black) connects to N- with relay. Pin 4 (Yellow Green) connects to tank ground.
- Low (Min.) Mode: Pin 1 (Brown) connects to N-. Pin 2 (Black) connects to L+. To output, Pin 3 (Blue) connects to N- with relay. Pin 4 (Yellow Green) should contact to tank ground.

NPN Output

- High (Max.) Mode: Pin 1 (Brown) connects to L+. Pin 3 (Blue) connects to N-. To output, Pin 2 (Black) connects to L+ with relay. Pin 4(Yellow Green) should contact to tank ground.
- Low(Min.)Mode: Pin1 (Brown) connects to N-. Pin 3 (Blue) connects to L+. To output Pin 2 (Black) connects to L+ with relay. Pin 4 (Yellow Green) should contact To tank ground.

► M12 x 4Pin Wiring:

PNP Output

- High(Max.) Mode: No. 1 pin(Brown) is connected to L+. No.3 pin(Blue) is connected to N-. Output is connected to No. 2 pin(Green), then connected to N-.
- Low(Min.) Mode: number 1 pin(Brown) is connected to L+. No.3 pin(Blue) is connected to N-. Output is connected to No. 4 pin(Black), then connected to N-.


NPN Output

- High(Max.) Mode: No. 1 pin(Brown) is connected to L+. No.3 pin(Blue) is connected to N-. Output is connected to No. 2 pin(Green), then connected to L+.
- Low(Min.) Mode: No. 1 pin(Brown) is connected to L+. No.3 pin(Blue) is connected to N-. Output is connected to No. 4 pin(Black), then connected to L+.

WIRING INSTRUCTIONS (SC35)

WIRING CONFIGURATION DIAGRAM AND INTRODUCTION OF FEATURES


Dual-relay output



Load: External load
 $U \sim \text{max. } 250\text{Vac}@I_L \sim \text{max. } 6\text{A}$
 $U \sim \text{max. } 28\text{Vdc}@I_L \sim \text{max. } 6\text{A}$

Failure mode	Material level	Output signal			LED indicators		
		output1	output2		Power Green	Status Yellow	Alarm Red
MAX						O.S.	
						O.S.	
MIN						O.S.	
						O.S.	
Viscous material		Maintain the previous state				O.S.	
Wear of tuning fork							

Dual-transistor output



Load: External load
 $U \sim \text{max. } 60\text{Vac}@I_L \sim \text{max. } 350\text{mA}$
 $U \sim \text{max. } 60\text{Vdc}@I_L \sim \text{max. } 350\text{mA}$
 ※ External load R must be connected

Failure mode	Material level	Output signal			LED indicators		
		output1	output2		Power Green	Status Yellow	Alarm Red
MAX						O.S.	
						O.S.	
MIN						O.S.	
						O.S.	
Viscous material		Maintain the previous state				O.S.	
Wear of tuning fork							
Output1>350mA			Maintain the previous state				
Output2>350mA		Maintain the previous state					
Output1 & Output2>350mA							

※ When output is off, there will be no error current status


: ON : Flash : OFF

: Relay ON : Relay OFF I_L : Load current


WIRING INSTRUCTIONS (SC38)

WIRING CONFIGURATION DIAGRAM AND INTRODUCTION OF FEATURES


8/16mA output



PNP/NPN Output



Dual Relay output



Failure mode	Material level	Output signal	LED indicators
MAX		$\begin{matrix} + \\ 2 \end{matrix} \xrightarrow{\sim 16mA} 1$	O.S. F.S.
		$\begin{matrix} + \\ 2 \end{matrix} \xrightarrow{\sim 8mA} 1$	O.S. F.S.
MIN		$\begin{matrix} + \\ 2 \end{matrix} \xrightarrow{\sim 16mA} 1$	O.S. F.S.
		$\begin{matrix} + \\ 2 \end{matrix} \xrightarrow{\sim 8mA} 1$	O.S. F.S.
Instrument failure		$\begin{matrix} + \\ 2 \end{matrix} \xrightarrow{<3.6mA} 1$	

$\sim 16mA = 16mA \pm 5\%$

$\sim 8mA = 8mA \pm 5\%$

: ON : Flash : OFF

Failure mode	Material level	Output signal	LED indicators
MAX		$\square \xrightarrow{I_L} \square$	O.S. F.S.
		$\square \xrightarrow{<100\mu A} \square$	O.S. F.S.
MIN		$\square \xrightarrow{I_L} \square$	O.S. F.S.
		$\square \xrightarrow{<100\mu A} \square$	O.S. F.S.
Instrument failure		$\square \xrightarrow{<100\mu A} \square$	
Over Load ($I_L > 350mA$)		$\square \xrightarrow{<100\mu A} \square$	

I_L : Load current

R : External load

U = max. 55Vdc @ I_L = max. 350mA

: ON : Flash : OFF

Failure mode	Material level	Output signal	LED indicators	
			PWR	SIG
MAX		$\begin{matrix} NO1 & COM1 & NC1 \\ NO2 & COM2 & NC2 \end{matrix}$	O.S. F.S.	
		$\begin{matrix} NO1 & COM1 & NC1 \\ NO2 & COM2 & NC2 \end{matrix}$	O.S. F.S.	
MIN		$\begin{matrix} NO1 & COM1 & NC1 \\ NO2 & COM2 & NC2 \end{matrix}$	O.S. F.S.	
		$\begin{matrix} NO1 & COM1 & NC1 \\ NO2 & COM2 & NC2 \end{matrix}$	O.S. F.S.	
Instrument failure		$\begin{matrix} NO1 & COM1 & NC1 \\ NO2 & COM2 & NC2 \end{matrix}$		

R: External load

U ~ max. 250Vac @ I_L ~ max. 6A

U = max. 28Vdc @ I_L = max. 6A


: ON : Flash : OFF

TUNING AND INDICATION DETAILS

FORK TRIGGER POINT


SC1X/SC24 fork trigger point is shown as below figure.

The testing medium is water ($S.G.=1 \text{ g/cm}^3$), and its trigger point is about 23mm from the fork tip. If testing medium with S.G (specific gravity) lower than 1g/cm^3 (water), the trigger point would increase. Similarly, the trigger point will downward while the S.G is large than water.



MAGNETIC TEST

After the switch is installed and powered, magnetic test function can be performed accordingly. The testing point is marked on the housing label. User holds the magnet and moves it close to testing point, the output status will switch from NO. to NC. or NC to NO. and red LED would switch ON or OFF while fork continues to vibrate. When magnet is pulled away from the testing point, the output status and red LED would return as default while fork continues to vibrate. The purpose of testing is to confirm the wiring and functioning are correct.



TUNING AND INDICATION DETAILS(LITE-TYPE/MINI-TYPE)

Output Status For Relay

- Low (Min.) Mode: Tuning fork switch will be active after 3 seconds while power on. Relay is on NO status and red LED indication is off. When tuning fork is covered by testing medium, the vibration will stop and relay becomes NC status. Red LED indication then is on.
 - High(Max.) Mode: Tuning fork switch will be active after 3 seconds while the power on. Relay is on NC status and red LED indication is on. When tuning fork covered by testing medium, the vibration stops and relay becomes NO status. Red LED indication is on.
- Flashing red indicates abnormal: Possible causes overloads or short-circuit load back, equipment malfunction or wear tuning fork probe.

	Min. Mode		Max.Mode		
Level					Instrument failure
Contactless electronic switch	 Switch open	 Switch closed	 Switch closed	 Switch open	 Switch open
Red LED					

 It represents Blinking

Output Status For PNP / NPN Transistor

DIN & Cable type

- Low(Min.) Mode: Tuning fork switch will be active after 3 seconds while power on. Output transistor is on NO status and red LED indication is on. When tuning fork covered by testing medium,vibration will stop and output transistor becomes NC status. Red LED indication is off.
 - High(Max.) Mode: Tuning fork switch will be active after 3 seconds while power on. Output transistor is on NC status and red LED indication is on. When tuning fork covered by testing medium,vibration will stop and output transistor becomes NO status. Red LED indication is off.
- Flashing red indicates abnormal: Possible causes overloads or short-circuit load back, equipment malfunction or wear tuning fork probe.

M12 x 4Pin type

■

■


■

	Min. Mode		Max.Mode		
Level					Instrument failure
PNP/NPN Output	 Switch open	 Switch closed	 Switch closed	 Switch open	 Switch open
Red LED (DIN& Cable)					
Red LED (M12x 4Pin)					

 It represents Blinking

DESCRIPTION OF FEATURES (SC35)

PANEL INTRODUCTION




- ①: Test button
- ②: Function adjustment button
- ③: Power indicator
- ④: Status indicator
- ⑤: Alarm indicator



Abbreviation	Function	Option description	Remarks
Test	Test button	Reverse the signal output	It is for the test after the installation is completed.
F.S.	Fail-Safe	MAX: High MIN: Low	It is for the high and low Fail-Safe mode.
D.T.	Delay Time	S: General setting L: Delay for 5 seconds	Covered by material: 0.5s Not covered by material: 150°C: ≤1.5s 230°C / 280°C: ≤2s Switch to L to set it at 5 seconds for either covered or not covered by material.
S.G.	Specific Gravity	H: ≥0.05 g/cm ³ L: ≥0.01 g/cm ³	The switch to set the material density.
S.D.	Self Diagnosis	OFF: Disabled ON: Enabled	Detect the wear of the tuning fork or the viscous material and control the ON/OFF of the alarm indicator
S.S.	Super Switch	OFF: Disabled ON: Enabled	Switch the second set of output switch to the alarm indicator of the wear of the tuning fork or the viscous material for output
S.I.	Signal Indication	F.S.: Fail-Safe mode O.S.: Output mode	Turn ON/OFF the yellow indicator based on the output status or the fail-safe status.

SEDIMENT DETECTION

- It is only used to detect the sediment under the water, but can't be used for the level detection of the liquid or the doped liquid.
- S.G. (Specific Gravity) shall be adjusted to H position.
- S.D. (Self Diagnosis) shall be switched to OFF position.
- SC352 cable type is inapplicable to this working environment




ENVIRONMENT/PROCESS TEMPERATURE LIMITATION



- ※ ETFE coating: T_p max.=150°C
- ※ PTFE coating: T_p max.=230°C

DESCRIPTION OF FEATURES (SC38)

PANEL INTRODUCTION



- ①: Test button
- ②: Operation point calibration button
- ③: Function adjustment button
- ④: Power indicator
- ⑤: Status indicator


Abbreviation	Function	Option Description	Remarks
Test	Test button	Reverse the signal output	It is for the test after the installation is completed.
F.S.	Fail-Safe	MAX: High MIN: Low	It is for the high and low Fail-Safe mode.
D.T.	Delay Time	S: General setting L: Delay for 5 seconds	Covered by material: Approx. 0.5s Not covered by material: Approx. 1s Switch to L to set it at 5 seconds for either covered or not covered by material.
S.G.	Specific Gravity	H: $\geq 0.7 \text{ g/cm}^3$ L: $\geq 0.5 \text{ g/cm}^3$	The switch to set the material density.
S.I.	Signal Indication	F.S.: Fail-Safe mode O.S.: Output mode	Turn ON/OFF the yellow indicator based on the output status or the fail-safe status.

DESCRIPTION OF THE TEST BUTTON

This button is mainly provided for the user to check whether the output operation works normally after the installation is completed. When the button is pressed, the output current (8mA $\leftrightarrow$ 16mA) and indicator (ON $\leftrightarrow$ OFF) will be reversed. Once the button is released, it will recover the original status.

FUNCTION OF CUSTOMIZED OPERATION POINT POSITION

SC38 provides the function of customizing the operation point position according to what is required by the user.



Settings

1. Keep pressing "Calibration Button" for 3 seconds. When the red and green LED indicators flash every 0.5 second, it enters the calibration mode. Press the calibration button again to enter the Empty Bin Calibration mode.

[Empty Bin Calibration]

2. Calibration status: The red LED indicator flashes every 0.5 second, and the output current switches to operate every 0.5 second (8 $\leftrightarrow$ 16mA).

3. This mode is to calibrate the vibration frequency of the tuning fork in the air. Press "Calibration Button" when the tuning fork doesn't touch any material. The unit will record the vibration frequency in the air, and enter the operation point calibration mode.

[Operation Point Calibration]

1. Calibration status: The red LED indicator flashes every 0.25 second, and the output current switches to operate every 0.25 second (8 $\leftrightarrow$ 16mA).


2. Cover the material to the desired operating point position under this mode, and then press "Calibration Button". It will be adjusted to the corresponding operating point position according to the H/L setting of the S.G.

DESCRIPTION OF FEATURES (SC38)


FORK TRIGGER POINT

The position of the SC38 fork trigger point depends on the mounting position as shown in the figure below: (When the testing medium is water, S.G.=1 g/cm³, the distance of the trigger point is 13mm). If the testing medium has an S.G lower than 1g/cm³, the trigger point would rise. Similarly, the trigger point will move downward while the S.G is greater than water. The moving distance is subject to the S.G.

※Operating point position: ◀



ENVIRONMENT AND PROCESS TEMPERATURE LIMITATION



MODEL NUMBER / ORDER CODE COMPARISON TABLE

Model Number	Order Code
SC1400	SCX10000-AAB
SC1410	SCX10000-CAB
SC1420	SCX10000-BAB
SC1740	SCX1001C-AAB
SC1741	SCX1001C-CAB

SC2400	SCX2□□00-□BA
SC240□□T	SCX20200-□BA
SC24P□	SCX2□□00-□BP
SC24N□	SCX2□□00-□BN
SC2800	SCX2□□00-□AA
SC280□□T	SCX20200-□AA
SC28P□	SCX2□□00-□AP
SC28N□	SCX2□□00-□AN

SC350	SCX3□□□□-EC(HC,JC)
SC351	SCX3□□□□-FC(IC,KC)
SC352	SCX3□□□□-DC
SC380	SCX3□□□□-AA(EA)
SC381	SCX3□□□□-BA(FA)
SC382	SCX3□□□□-CA(GA)

ORDER INFORMATION

STANDARD-TYPE

SCX1 ⁰⁵☐ ⁰⁶☐ ⁰⁷☐ ⁰⁸☐ - ⁰⁹☐ A B ¹²☐ ¹³☐ ¹⁴☐ ¹⁵☐ ¹⁶☐ ¹⁷☐ ¹⁸☐ ¹⁹☐ ²⁰☐ ²¹☐ ²²☐ ²³☐ ²⁴☐ ²⁵☐ ²⁶☐

⁰⁵ ⁰⁶ Model

00: Standard
03: Sanitary

⁰⁷ ⁰⁸ Certification

00: None
1C: ATEX-Ex d
2C: IECEx-Ex d
7C: NEPSI-Ex d
5C: TS-Ex d

⁰⁹ Construction

A: Standard E: Anti-Corrosion probe type
B: Extended type F: Anti-Corrosion extended probe type
C: Lengthened type G: Sanitary joint type
D: Cable type

¹² Power supply

C: 20~250Vac/Vdc, 50/60Hz ; Relay O/P - Euro terminal
D: 20~250Vac/Vdc, 50/60Hz ; SSR(MOSFET) - Euro terminal
E: 20~250Vac/Vdc, 50/60Hz ; Relay O/P*2 - Euro terminal
F: 20~250Vac/Vdc, 50/60Hz ; SSR(MOSFET)*2 - Euro terminal

Connection

¹³ ¹⁴

Flange
AK: JIS-FF
AN: ANSI-RF
AS: DIN-FF
AI: 3A

Thread

AA: JIS
AC: ANSI

¹⁵ ¹⁶

A8: 1"
A9: 1-1/4"
B1: 1-1/2"
B2: 2"
B4: 2-1/2"
B5: 3"
B7: 4"
D8: DN25
E1: DN40

¹⁷ ¹⁸

01: PT male
03: PF male
07: NPT male
40: 5 kg/cm²
42: 10 kg/cm²
48: 150 Lbs
49: 300 Lbs
57: PN10
58: PN16

(Next page)

ORDER INFORMATION

SCX1 ⁰⁵ ⁰⁶ ⁰⁷ ⁰⁸ ⁰⁹ - ¹² ¹³ ¹⁴ ¹⁵ ¹⁶ ¹⁷ ¹⁸ ¹⁹ ²⁰ ²¹ ²² ²³ ²⁴ ²⁵ ²⁶ A B

¹⁹ ²⁰ **Probe material**

MA: SUS304
MB: SUS316
MC: SUS316L

²¹ ²² **Coating material**

00: None
14: PFA
34: ECTFE
※ Coating length max. 400mm

²³ ²⁴ ²⁵ ²⁶ **Probe length**

Code	Probe Length
0001~9999	0001~9999mm

ORDER INFORMATION

LITE-TYPE/MINI-TYPE

SCX2 05 06 0 0 - 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24

⑤⑥ Model

00: Standard
02: Hi-temperature
03: Sanitary

⑨ Construction

A: Standard
B: Extended type

⑩ Fork length

A: 40mm
B: 100mm

⑪ Power supply

A: 20~250Vac/Vdc, 50/60Hz; 2 wire Contactless electronic switch
P: 12~55Vdc ; 3 Wire PNP output.
N: 12~55Vdc ; 3 Wire NPN output.

Connection

⑫⑬

Flange
AK: JIS-FF
AN: ANSI-RF
AS: DIN-FF
AI: 3A

⑭⑮

A7: 3/4"
A8: 1"
A9: 1-1/4"
B1: 1-1/2"
B2: 2"
B4: 2-1/2"
B5: 3"
B7: 4"
D8: DN25
E1: DN40

⑯⑰

01: PT male
03: PF male
07: NPT male
40: 5 kg/cm²
42: 10 kg/cm²
48: 150 Lbs
49: 300 Lbs
57: PN10
58: PN16

⑱⑲ Probe material

MA: SUS304
MB: SUS316
MC: SUS316L

⑳ Connection

A: M12x1(180°) C: Cable
B: M12x1(90°) D: DIN 43650

㉑㉒㉓㉔ Probe length

Code	Probe Length
0076~0250	0076~0250mm

ORDER INFORMATION

MULTI-FUNCTIONAL-TYPE SCX3 ☐ ⁰⁵☐ ⁰⁶☐ ⁰⁷☐ ⁰⁸☐ - ☐ ⁰⁹☐ ☐ ¹⁰☐ ☐ ¹¹☐ ☐ ¹²☐ ☐ ¹³☐ ☐ ¹⁴☐ ☐ ¹⁵☐ ☐ ¹⁶☐ ☐ ¹⁷☐ ☐ ¹⁸☐ ☐ ¹⁹☐ ☐ ²⁰☐ ☐ ²¹☐ ☐ ²²☐ ☐ ²³☐ ☐ ²⁴☐ ☐ ²⁵☐ ☐ ²⁶☐ ☐ ²⁷☐ ☐ ²⁸

⁰⁵ ⁰⁶ **Model** _____

- 00: Standard
(Construction: A, B, C, D)
- 02: Hi-temperature
(Construction: E, F, G)
- 09: High temperature type 2
(Construction: J, K)

⁰⁷ ⁰⁸ **Certification** _____

- 01: None; 1/2" PF
- 02: None; 1/2" NPT
- 03: None; M20x1.5
- 2D : IECEx-Ex t : 1/2"NPT
- 5D: TS-Ex t; 1/2" NPT
- 7B: NEPSI-Ex ia; 1/2" NPT
- 7D: NEPSI-Ex d; 1/2" NPT

⁰⁹ **Construction** _____

- A: Standard (150°C @ 50°C)
- B: Extended type (150°C @ 50°C)
- C: Lengthened type (150°C @ 50°C)
- D: Cable type (80°C)
- E: High temperature general type
(150°C @ 85°C)
- F: High temperature extension type
(150°C @ 85°C)
- G: High temperature lengthening type
(150°C @ 85°C)
- J: High temperature type 2 (280°C)
- K: High temperature extended type 2 (280°C)

¹⁰ **Fork length** _____

- A: 40mm(SC38)
- C: 155mm(SC35)

¹¹ **Housing** _____

- F: Aluminum
- R: stainless steel (No explosion protection)

¹² **Housing cover** _____

- A: No Lens
- B: Lens(only stainless steel)

(Next page)

ORDER INFORMATION

SCX3 ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱ ⑲ ⑳ ㉑ ㉒ ㉓ ㉔ ㉕ ㉖ ㉗ ㉘

⑬ Power supply

A: 19~253Vac/Vdc, 50/60Hz; Two Relay output
 B: 19~253Vac/Vdc, 50/60Hz; Two Transistor output
 C: 10~55Vdc; 3 wire PNP/NPN Output
 D: 11~36Vdc; 8/16mA Output

Connection

⑭ ⑮

Flange
 AK: JIS-FF
 AN: ANSI-RF
 AS: DIN-FF
 AI: 3A

Thread

AA: JIS
 AC: ANSI

⑯ ⑰

A7: 3/4"
 A8: 1"
 A9: 1- 1/4"
 B1: 1-1/2"
 B2: 2"
 B4: 2-1/2"
 B5: 3"
 B7: 4"
 D8: DN25
 E1: DN40

⑱ ⑲

01: PT male
 03: PF male
 07: NPT male
 40: 5 kg/cm²
 42: 10 kg/cm²
 48: 150 Lbs
 49: 300 Lbs
 57: PN10
 58: PN16

㉑ ㉒ Probe material

MA: SUS304
 MB: SUS316
 MC: SUS316L

㉓ ㉔ Coating material

00: None
 14: PFA
 21: PTFE
 34: ECTFE
 36: ETFE

※ Coating length max. 400mm

㉕ Surface roughness

A: Ra ≤ 3.2um
 B: Ra ≤ 1.5um
 C: Ra ≤ 0.8um
 D: Ra ≤ 0.3um

㉖ ㉗ ㉘ ㉙ Probe length

Code	Probe Length
0075	75mm
0225~4000	225~4000mm
0750~A200	750~20000mm
0120~3000	120~3000mm

Global Network



■ Head Quarter

● Taiwan

FineTek Co., Ltd. - Taipei Head Quarter 
No.16, Tzuchiang St., Tucheng Industrial Park
New Taipei City 236, Taiwan
TEL: 886-2-2269-6789
FAX: 886-2-2268-6682
EMAIL: info@fine-tek.com

■ North America

● California, U.S.

Aplus Finetek Sensor Inc. - US Office
355 S. Lemon Ave, Suite D
Walnut, CA 91789
TEL: 1 909 598 2488
FAX: 1 909 598 3188
EMAIL: info@aplusfine.com

■ Europe

● Germany

FineTek GmbH - Germany Office
Bei den Kämpen 26
21220 Seevetal-Ramelsloh, Germany
TEL: +49-(0)4185-8083-12
FAX: +49-(0)4185-8083-80
EMAIL: info@fine-tek.de

■ Asia

● China

Fine automation Co., Ltd. - Shanghai Factory 
No.451 DuHui Rd, MinHang District, Shanghai,
China 201109
TEL: 86-21-6490-7260
EMAIL: info.sh@fine-tek.com

● Singapore

FineTek Pte Ltd. - Singapore Office
37 Kaki Bukit Place, Level 4 Singapore 416215
TEL: 65-6452-6340
EMAIL: info.sg@fine-tek.com

● Indonesia

PT. FineTek Automation Indonesia - Indonesia Office 
PERGUDANGAN TUNAS BITUNG
JL. Raya Serang KM. 13,8, Blok C3 No. 12&15, Bitung Cikupa,
Tangerang 15710
TEL: 62 (021)-2958-1688
EMAIL: info.id@fine-tek.com



Distributor: